

NC WINDSCREEN



APPLICATION INSTRUCTIONS



USE MASK



USE GLOVES



KEEP AWAY FROM
OPEN FIRE



MAKE SURE FOR
GOOD VENTILATION

INSTRUCTIONS AND USE SHOULD BE FOLLOWED
STRICTLY.



CONDITION OF SUBSTRATE

- The substrate to be coated must be completely clean, grease-free, and **absolutely dry**.
 - In contact with a damp substrate surface, it reacts prematurely and cannot form a permanent seal.
 - The substrate temperature must be between 41° F / 86° F, the relative humidity at 30-60 %.
 - Keep away from open fire and make sure for proper ventilation.
 - Do not apply **under sunlight**.
 - Do not apply in **damp or very humid** conditions.
 - Do not use the coating in **hot surfaces**.
 - Do not apply in windscreens or windows which has been coated previously (Remove old residues).
-



DANIEL@DCIFILMS.COM
305-640-0295
WWW.DCIFILMS.COM

7866 NW 62ND STREET
MIAMI, FL 33166, USA

NC WINDSCREEN



PREPARATION

STEP 1

- We recommend that the glass surface is **spotlessly clean, washed with water, and neutral cleaner.**
- Thoroughly rinse the windshield surface with **clear water** (without cleaner) to remove cleaner residues.
- Dry the glass surface with an absorbent clean cloth.
- Repeat **Step one (1)** step until the cloth is no dirt or grime.
- Make sure the windscreen is dry, free of grease, dust, etc. (**use alcohol basic and neutral cleaners non-acids**).
- Use alcohol genuinely to clean any residues of previous cleaners (Follow MSDS instructions for alcohol use).

Do not consider that the windshield is clean only by wiping and drying. On average it takes minimum 10 minutes to clean a windscreen por correct application



APPLICATION

STEP 2

- Use pre-impregnated lint-free cloth 0.34oz Which is the approximately optimal amount for a 10 x 10 inches.
 - After glass preparation. Use recommended **quantity** to prevent non transparent surfaces.
 - Ensure full coverage and **work quickly** with both vertical and horizontal actions
 - Be sure to clean wiper edge then wipe the coating cloth along with the wiper rubber.
-



NC WINDSCREEN



FINISHING

STEP 3

- Leave the solution remains on the surface for **(45) minutes**.
 - The surface may look "cloudy" after drying time.
 - Removed silane residues, buff the surface with a clean and dry soft microfiber cloth or clean and dry kitchen roll preferably.
-



CURING

STEP 4

- The product takes **ten (10) hours** to cure fully.
 - The surface can be exposed to water or rain **two (2) hours** after application.
 - The effect of the products will last at least **eight (8) months**.
-

Recommendation: The water tank for Windscreen Cleaner should be filled with clear water or a mild cleaner.

COMPLETE TECHNICAL DATA & SAFETY MEASURES ON TDS, ASK YOUR DISTRIBUTOR IF NECESSARY.



DANIEL@DCIFILMS.COM
305-640-0295
WWW.DCIFILMS.COM

7866 NW 62ND STREET
MIAMI, FL 33166, USA